
ASSEMBLY INSTRUCTION MANUAL
#60-421 DOUBLE RAIL SALESMAN RACK IVORY




9801 PAGE AVENUE
ST. LOUIS, MO. 63132-1428
TEL: (314) 427-8887
or (800) 823-8887
FAX: (314) 427-0004
or (800) 823-0004

STORE SUPPLY Warehouse LLC

#60-421 ASSEMBLY INSTRUCTIONS

DOUBLE RAIL SALESMAN RACK IVORY


PARTS IN CARTON:




TOP CROSSBAR
1 EACH




ROUND CROSS BAR
2 EACH




BOTTOM CROSSBAR
2 EACH




EXTENSION SUPPORT BAR
2 EACH



"T" BAR
2 EACH



LOCK WHEEL
2 EACH



WHEEL
2 EACH


STORE SUPPLY Warehouse LLC

RESUME FOR HARDWARE NEEDED


#60-421 ASSEMBLY INSTRUCTIONS
DOUBLE RAIL SALESMAN RACK IVORY

HARDWARE AND TOOLS IN BAG:


NOTE: HARDWARE BELOW IS SHOWN AT ACTUAL SIZE. IF YOU ARE NOT SURE WHICH PART IS CORRECT, THEN PLACE PIECE ON TOP OF DRAWING BELOW FOR HELP DURING ASSEMBLY.




2" ALLEN HEAD SCREW
8 EACH



3/4" WASHER
8 EACH



3/4" LOCK WASHER
4 EACH




1/4" ALLEN WRENCH
1 EACH


RESUME FOR STEP BY STEP INSTRUCTIONS

#60-421 ASSEMBLY INSTRUCTIONS
DOUBLE RAIL SALESMAN RACK IVORY

STEP 1:
LOCATE (2) TWO SCREWS, (2) TWO WASHERS, (1) ONE "T" BAR AND (2) TWO BOTTOM CROSSBARS.







STEP 2: (SEE FIGURE 1)
LOCATE THE HOLES ON THE BOTTOM END OF THE "T" BAR. PLACE (1) ONE WASHER ON A SCREW AND THEN SLIDE THE SCREW THROUGH HOLE. USING THE ALLEN WRENCH, SCREW THE REMAINING END OF THE SCREW INTO ONE END OF THE BOTTOM CROSS BAR.

NOTE: THE VERTICAL HOLES ON THE TOP OF THE "T" BAR SHOULD BE FACING INWARD.





FIGURE 1

STEP 3 :
REPEAT STEPS 1 AND 2 FOR REMAINING THREE HOLES TO COMPLETE THE BOTTOM BASE OF THE DOUBLE RAIL SALESMAN RACK.




STORE SUPPLY Warehouse LLC

#60-421 ASSEMBLY INSTRUCTIONS

DOUBLE RAIL SALESMAN RACK IVORY

STEP 4:
LOCATE (2) TWO WHEELS, (2) TWO WHEELS WITH LOCKS AND (4) FOUR LOCK WASHERS.

NOTE: REMOVE THE NUTS BEFORE MOVING ON TO NEXT STEP.



STEP 5: (SEE FIGURE 2)
TILT THE RACK OVER TO ACCESS THE BOTTOM SCREW HOLES. PLACE (1) ONE WASHER ON THE TOP BOLT OF WHEEL THEN SCREW WHEELS CLOCKWISE INTO THE SCREW HOLES.





FIGURE 2

STEP 6:
REPEAT STEP 5 USING THE LOCKING WHEELS TO COMPLETE THE WHEEL ASSEMBLY.




RESUME TO CONCLUDE ASSEMBLY

#60-421 ASSEMBLY INSTRUCTIONS


DOUBLE RAIL SALESMAN RACK IVORY

STEP 7:
LOCATE (2) TWO EXTENSION SUPPORT BARS.





STEP 8: (SEE FIGURE 3)
SLIDE IN THE EXTENSION SUPPORT BAR INTO THE SHAFT OF THE "T" BAR BY PUSHING IN THE METAL PIN AND SLIDING DOWN THE EXTENSION SUPPORT BAR.

FIGURE 3B



STEP 9:
REPEAT STEP 8 FOR REMAINING EXTENSION CROSSBAR.






STORE SUPPLY Warehouse LLC


#60-421 ASSEMBLY INSTRUCTIONS
DOUBLE RAIL SALESMAN RACK IVORY

STEP 10:
LOCATE (4) FOUR SCREWS AND (2) TWO ROUND POLES.




STEP 11: (SEE FIGURE 4)
LOCATE THE HOLE ON THE OUTER END OF THE EXTENSION SUPPORT BAR. PLACE ONE WASHER ON A SCREW AND THEN SLIDE SCREW THROUGH HOLE. USING THE ALLEN WRENCH, SCREW THE REMAINING END OF THE SCREW INTO ONE END OF THE ROUND POLE.

FIGURE 4




STEP 12:
REPEAT STEP 10 FOR THE THREE REMAINING SIDES.



#60-421 ASSEMBLY INSTRUCTIONS
DOUBLE RAIL SALESMAN RACK IVORY

STEP 13:
LOCATE THE TOP CROSS BAR.



1 (ea.)

STEP 14: (SEE FIGURE 5)
PRESS IN THE METAL CLIPS ON THE EXTENSION SUPPORT BAR AND SLIDE THE TOP CROSSBAR OVER THE EXTENSION SUPPORT BAR UNTIL THE METAL CLIPS SNAP INTO PLACE.

REPEAT FOR OPPOSITE SIDE.





FIGURE 5

NOTE: MAKE SURE ALL BOLTS AND SCREWS ARE SECURED TIGHTLY BEFORE HANGING MERCHANDISE.



STORE SUPPLY Warehouse LLC